



S11

BONDING CORNICE

ADHESIVE 2 IN 1



UNIVERSAL USAGE

- Designed for all phases of fibrous plasterboard jointing
- Designed for all phases of cornice fixing
- Covering screws & nails
- Filling or patching holes

PRODUCT FEATURES

- Excellent workability
- Easy mix
- Extra high bonding strength
- Low shrinkage
- High crack resistance
- Excellent for covering cracks
- Smooth finishing
- Covers holes, screws and nails

PACKAGING

- 20 kg



S11 Bonding Cornice Adhesive 2-in-1

Product Information

S11 Bonding Cornice Adhesive 2-in-1 is a high performance gypsum based compound made for bonding cornice to plasterboards, ceilings and walls. The compound is great for direct bonding of cornice and fixing of cornice at all phases as it has a high adhesive and bonding strength. Its low shrinkage also allows it to act as a stopping compound, providing a smooth finish when flushing plasterboard joints.

Features

- Excellent workability
- Easy mix
- Extra high bonding strength
- Low shrinkage
- High crack resistance
- Excellent for covering cracks
- Smooth finishing
- Covers holes, screws and nails

Preparation

- Fill clean water into empty container.
- Add S11 Bonding Cornice Adhesive 2-in-1 at a ratio of 2 volumes of dry powder to 1 volume of water. Allow to soak for minimum of 1 minute.
- Mix thoroughly to achieve a thick creamy paste of smooth workable consistency.
- Do not over-mix. Over-mixing can cause air bubbles to form and hence, creating an imperfect surface.

Application

- Can be applied using broad knife or trowel.
- Apply S11 bonding compound mixture along the back edge of the cornice
- Place cornice at its intended position and press it against the wall or ceiling.
- Remove excess with broad knife or a damp sponge/brush.
- Use mixture to touch up on any imperfections in the cornice.
- Mixture can be used to fill and finish gaps, cracks, holes and joint.

Product Data	
Colour	White
Appearance	White powder
Flammability	Non-flammable
Solubility (water)	Soluble
Setting Time	25 minutes
Coverage	40m ² per 20kg bag (based on 3 coats application method)
Packaging	20kg
Shelf Life	6 months (from production date)



Precautions

- Surfaces must be dry, clean and free from dust.
- All tools should be clean before work commences.
- Contamination from previous mixes can shorten the setting time and in turn reduce the finished strength and quality of the product.
- Do not apply in areas subject to continuously damp or humid conditions.
- Do not apply over joints that are not thoroughly dry. Pinholes may result.

Storage

- Stored in dry and shaded condition
- Protected from extreme temperature.
- Storage in an unsuitable condition can shorten the life this product.
- Product should not be exposed to temperatures above 50°C for prolonged periods

Health and Safety

- Dust generated from this product contains silica. Prolonged inhalation maybe harmful to health.
- Use suitable dust mask and make sure the area is well ventilated.
- Avoid contact with eye. If comes into contact with eye, wash immediately with plenty of clean water and seek medical advice. Suitable eye protection is recommended.
- Avoid ingestion. In the event of ingestion, rinse with lots of clean water and drink plenty of water.
- Avoid prolonged contact with skin. Wash off with water.



Yoke Mah Plasterceil Pte Ltd
18 Tampines Industrial Crescent #03-02
The Space @ Tampines Singapore 528605
Tel : 6484 6679
Fax : 6858 6090