



S11

Render Plaster (387)

墙壁找平砂浆(387)

UNIVERSAL USAGE 用途

- High-performing plaster designed for productivity
专为提高效率而设计的高性能抹灰
- Excellent durability for internal and external walls
优异的耐久性适合室内和室外墙
- Suitable for brickwork, lightweight concrete and concrete blocks and substrate
适用于砖砌体、轻质混凝土、混凝土块和基材



Enhance Productivity
提高工作效率



Crack Resistance & Lasting Finish
抗裂性和持久性



Superior Bonding Strength
卓越的粘合强度



4260, Jalan Kilang Kelapa Sawit,
32400 Ayer Tawar, Perak, Malaysia



+605 6726176
/ 9315 / 5127



enquiry@fongyiindustries.com



FONG YI INDUSTRIES



S11 Render Plaster (387)

Product Information 产品资料

S11 Render Plaster (387) is a high-performing and lasting wall render solution that greatly increases productivity. The proprietary premixed formula is easy to use and has versatile applications. It allows for efficient bedding, wall tiling, repair and patching of non-structural concrete, enhancing surfaces of walls such as brick, lightweight concrete and concrete walls. **S11墙壁找平砂浆(387)**是一个高性能、持久的墙面抹灰方案，可大大提高效率。专有的预混配方使用方便，用途广泛。它可以有效地进行垫层、墙面贴砖、非结构性混凝土的修补，抹平砖墙、轻质混凝土墙和混凝土墙等墙面的表面。

Features 特征

- Excellent Bond Strength 优异的粘合强度
- Highly Workable Plaster 高和易性
- Easy to use 容易使用
- Crack & Water Resistant 抗裂抗水
- Highly versatile 多用途功能
- Suitable for internal & external surfaces
适合室内和室外表面

Product Data 产品数据	
Colour 颜色	Gray 灰色
Appearance 外观	Gray Powder 灰色粉末
Flammability 易燃	Non-Flammable 不易燃
Setting Time 凝固时间	40 - 60 minutes
Thickness 厚度	Up to 20mm 10mm per coat 一层
Coverage 覆盖范围	25-30m ² /mm per 40kg bag
Packaging 包装	40 kg
Shelf Life 保质期	12 months (from production date) (自生产日期起)

Precaution 预防

- Substrates must be clean and free from dust.
- Where necessary, particularly on highly absorptive or hot surfaces, moisten the substrate prior to application.
- All tools should be clean before work commences.
- Tools and substrate should be free of any particles such as grease, mould and dirt.
- 基材必须清洁且无灰尘。
- 必要时，特别是在吸水性强或高温的表面上，涂抹前应先湿润基材。
- 工作开始前，所有工具均应清洁。

Health and Safety 健康和安全

Avoid contact with eyes or swallowing of product. In case of contact with eyes, rinse immediate with plenty of water. If irritation persists, seek medical assistance. 避免接触眼睛或吞咽产品。如果接触眼睛，请立即用大量水冲洗。如果刺激持续存在，请寻求医疗帮助。

Preparation 准备

- Fill a container with clean water.
- Add **S11 Render Plaster (387)** at a ratio of 40 kg of dry powder to 5.5-7.5 litres of water.
- Mix thoroughly for 3-5 minutes to achieve a smooth workable consistency.
- Ensure the mix is lump-free and homogeneous.
- 将干净的水装容器。
- 按40公斤**S11墙壁找平砂浆(387)**干粉的比例添加至5.5 - 7.5升水。
- 彻底混合3-5分钟以达到浓稠状、可操作稠度的糊状物。
- 确保混合无结块且均匀。

Application 应用

- Can be applied using a trowel or broad knife.
- Apply a coat onto wall surface to ensure that the surface is even.
- Several layers can be applied to achieve the desired thickness. Ensure that the coat is dry before applying subsequent layers.
- For a smooth finish, apply S11 Walcoat(388) subsequently.
- 可用抹子或宽刀涂抹。
- 在墙面上涂一层，确保表面均匀。
- 可涂抹几层以达到所需的厚度。确保涂层干透后再涂下几层。
- 若要获得平滑表面，可随后使用S11 Walcoat (388)。

Storage 存储

- Stored in dry and shaded condition.
- Protected from extreme temperature.
- Storage in an unsuitable condition can shorten the shelf life of the product.
- 储存于干燥、阴凉处。
- 免受极端温度影响。
- 在不合适的条件下储存会缩短使用寿命产品的保质期。