



S11

WHITE FINISH (113)

UNIVERSAL USAGE 用途

- Elevated aesthetics for finishing of wall surfaces to provide walls to be painted or finished.
提高墙面装饰的美观性，以提供待涂漆或饰面的墙壁。
- Suitable for finishing concrete substrates
适用于修整混凝土基面
- Great bonding strength and low shrinkage for a crack-resistant finish
粘合强度高，收缩率低，可实现抗裂



Superior Aesthetics and Smoothness
卓越的美感和光滑度



Crack Resistance & Lasting Finish
抗裂性和持久性



Excellent Workability
高和易性



4260, Jalan Kilang Kelapa Sawit,
32400 Ayer Tawar, Perak, Malaysia



+605 6726176
/ 9315 / 5127



enquiry@fongyiindustries.com



FONG YI INDUSTRIES



S11 White Finish(113)

Product Information 产品资料

S11 White Finish(113) is a fine finishing skim coat, providing premium quality finish to internal wall and ceiling. It is designed to be applied on a diversity of substrates such as precast concrete, aerated concrete, block walls and plastered surfaces. It gives the surface an extremely fine and white finish which is suitable for painting.

S11 White Finish(113)是一种精细饰面腻子，可为内墙和混凝土楼板提供优质饰面。它设计用于多种基材，例如预制混凝土、加气轻装混凝土、砌块墙和抹灰表面。它赋予表面极其细腻和白色的光洁度，适合涂漆。

Features 特征

- Developed for finishing of walls & ceilings
专为墙壁和混凝土楼板的装饰而开发
- Highly Workable 高和易性
- Crack Resistant 抗裂
- Easy to use 容易使用
- Suitable for internal surfaces 适用于内表面
- Excellent Bond Strength 优异的粘合强度
- Consistency in quality 质量的一致性

Product Data 产品数据	
Colour 颜色	White 白
Appearance 外观	White Powder 白色粉末
Setting Time 凝固时间	> 60 minutes
Thickness 厚度	10mm
Coverage 覆盖范围	12-16m ² /mm per 20kg bag
Packaging 包装	20 kg
Product Standard 产品标准	BS 13279
Shelf Life 保质期	6 months (from production date) (自生产日期起)

Storage 存储

- Stored in dry and shaded condition.
- Protected from extreme temperature.
- Storage in an unsuitable condition can shorten the shelf life of the product.
- 储存于干燥、阴凉处。
- 免受极端温度影响。
- 在不合适的条件下储存会缩短使用寿命产品的保质期。

Health and Safety 健康和安全

Avoid contact with eyes or swallowing of product. In case of contact with eyes, rinse immediate with plenty of water. If irritation persists, seek medical assistance.

避免接触眼睛或吞咽产品。如果接触眼睛，请立即用大量水冲洗。如果刺激持续存在，请寻求医疗帮助。

Preparation 准备

- Fill a container with clean water.
- Add **S11 White Finish(113)** at a ratio of 20 kg of dry powder to 7.2-8 litres of water.
- Mix thoroughly for 1-2 minutes to achieve a thick creamy paste of smooth workable consistency.
- Do not over-mix. Over-mixing can cause air bubbles to form and hence, creating an imperfect surface.
- 将干净的水装容器。
- 按20公斤S11 White Finish(113)干粉的比例添加至7.2 - 8升水。
- 彻底混合1-2分钟以达到浓稠状具有光滑、可操作稠度的糊状物。
- 不要过度混合。过度混合会产生气泡形成并因此产生不完美的表面。

Application 应用

- Can be applied using a trowel or broad knife.
- Apply a coat onto wall surface and smoothen with a trowel
- Allow the coat to cure & dry for 60 - 80 minutes.
- 可以使用抹刀或阔刀进行施工。
- 在墙面上涂抹一层涂层，用抹刀进行平滑。
- 让涂层固化并干燥60-80分钟。

Precaution 预防

- Substrates must be clean and free from dust.
- All tools should be clean before work commences.
- Tools and substrate should be free of any particles such as grease, mould and dirt.
- 基材必须清洁且无灰尘。
- 工作开始前，所有工具均应清洁。
- 工具和基材应不含任何颗粒例如油脂、霉菌和污垢。